



HIGH-PRESSURE WASHERS - HOT WATER

# PW-H10

PRESSURE

120÷140  
bar

FLOW RATE

430÷450  
l/h

ABSORBED POWER

2,1÷2,5  
kW



PW-H10 P I 1408 AOM

### EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS
- ▶ BOILER IGNITION DELAY - IBD

### MOST FREQUENTLY USE

DIY AND GARDENING



### SPECS



LARGE FRONT FOOT FOR GREATER STABILITY



STURDY ERGONOMIC HANDLE FOR AN EASY MANOEUVRABILITY



4 LITRES DIESEL TANK MADE OF TRANSPARENT PLASTIC, IN ORDER TO ENSURE CONSTANT MONITORING OF DIESEL LEVEL

## TECHNICAL DATA

|                          | WITHOUT HOSE REEL             |                               | WITH HOSE REEL                 |
|--------------------------|-------------------------------|-------------------------------|--------------------------------|
|                          | PW-H10 I1207AA M<br>IDAC40572 | PW-H10 I1408AA M<br>IDAC40573 | PW-H10P I1408AO M<br>IDAC40574 |
| Code                     |                               |                               |                                |
| PERFORMANCE              |                               |                               |                                |
| Operating pressure       | bar/Mpa                       | 120/12                        | 140/14                         |
| Flow rate                | l/h                           | 430                           | 450                            |
| Outlet water temperature | °C                            | 60                            | 60                             |
| Power supply             | Ph-V-Hz/A                     | 1-230-50/9,4                  | 1-230-50/9,7                   |
| Absorbed power           | kW                            | 2,1                           | 2,3                            |
| Motor pole/rpm           |                               | 2-2800                        | 2-2800                         |
| Remote control           |                               | ITS                           | ITS                            |
| Pump/head/pistons        |                               | Axial/aluminium/inox          | Axial/aluminium/inox           |
| Boiler thermal power     | kW                            | 26                            | 26                             |
| Fuel consumption         | kg/h                          | 1,8                           | 1,9                            |
| Fuel tank                | l                             | 4                             | 4                              |
| Detergent tank           | l                             | -                             | -                              |
| Detergent delivery       |                               | low pressure                  | low pressure                   |
| Dimension (LxWxH)        | cm                            | 68x48x75                      | 68x48x75                       |
| Weight                   | kg                            | 44                            | 55                             |

## STANDARD EQUIPMENT

CODE: IPPR40017  
**HANDGRIP MV2009**  
(FOR I1207AA/I1408AA)



CODE: IPPR40020  
**HANDGRIP G6000**  
(FOR I1408AO)



CODE: LCPR40037  
**EXTENSION P50**  
**ZINC PLATED (FOR**  
**1207AA/1408AA)**



CODE: LCPR40071  
**LANCE WITH MULTIREG**  
**NOZZLE Ø 1,10**  
(FOR 1408AO)



CODE: UGLN49985  
**H.P NOZZLE 1/4 UG.1503**  
(FOR 1207)



CODE: UGLN75421  
**H.P NOZZLE 1/4**  
**UG.15025 (FOR 1408AO)**



CODE: TBAP28305  
**HIGH PRESSURE HOSE 8 m**  
(FOR I1207AA/I1408AA)



CODE: TBAP93872  
**HIGH PRESSURE HOSE 8 m**  
(FOR I1408AO)



CODE: LCPR40038  
**FOAMER M22**  
(FOR I1207AA/I1408AA)



CODE: LCPR40040  
**FOAMER M22 1 l**  
(FOR I1408AO)



CODE: LCPR40011  
**TURBO LANCE M22 D. 1,15**  
(FOR 1408AO)



## OPTIONAL ACCESSORIES

CODE: SPID24911  
**ROTATING HYDROBRUSH**  
**LANCE**



CODE: SPID24939  
**FIXED HYDROBRUSH**  
**LANCE**



CODE: TBAP23853  
**DRAIN KIT 10 m**



CODE: LCPR14857  
**SANDBLASTER KIT Ø 1,2 mm**  
(FOR 1408)



CODE: PRCH00065  
**SAND BAG 50 Kg**

