



GS 3/50 OPT

EXCLUSIVE FEATURES

- ▶ INNOVATIVE GASKET
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ DOUBLE STAGE MOTORS
- ▶ BIG AND BRAKED WHEELS
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE

GS 3/50 OPT

ASD015123

TECHNICAL DATA	
Code	ASD015123
Usage	DRY
Number of phases	single phase
Voltage	V 220-240
N. and type of motor	3x2 stages
Power	W 3000 - 3600 max
Water lift	mmH ₂ O 2470
Airflow	m ³ /h 630
Tank Capacity	l 50
Diameter of inlet	mm 60
Filtering surface	cm ² 12000 + 2260
Sound Pressure Level	dB(A) 76
Dimensions (LxWxH)	mm 580x700x1150
Weight	Kg 66

PLANET 1/50 OPT

EXCLUSIVE FEATURES

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ BIG AND BRAKED WHEELS
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ TURBINE WITH PERFECT PERFORMANCE

PLANET 1/50 OPT

ASID01200

TECHNICAL DATA	
Code	ASID01200
Usage	DRY
Number of phases	single phase
Voltage	V 230/50
N. and type of turbine	1x single stage
Power	W 1500
Water lift	mmH ₂ O 1800
Airflow	m ³ /h 220
Tank Capacity	l 50
Diameter of inlet	mm 60
Filtering surface	cm ² 12.000
Sound Pressure Level	dB(A) 74
Dimensions (LxWxH)	mm 600x660x1600
Weight	Kg 65

STANDARD EQUIPMENT

CODE: FTDP88585
POLYESTER MAIN FILTER
12.000 cm²



CODE: FTDP72142
CARTRIDGE FILTER
2260 cm²



CODE: FTDP00223
POLYCARBON PREFILTER



STANDARD EQUIPMENT

CODE: FTDP88585
POLYESTER MAIN FILTER
12.000 cm²



CODE: FTDP00223
POLYCARBON PREFILTER



OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436

OPTIONAL ACCESSORIES

Basic tool kit Ø38-60 mm	PMDT00325
Anti-Static tool kit Ø38-60 mm	PMDT00326
Basic tool kit Ø50-60 mm	PMDT00443
Anti-Static tool kit Ø50-60 mm	PMDT00436