



## PLANET OIL 3-PHASE

### EXCLUSIVE FEATURES

- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ BIG AND BRAKED WHEELS
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ ANTISKID WHEELS WITH BRAKES
- ▶ VISUAL FILLING INDICATOR
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ REVERSE FLOW FUNCTION
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE

### PLANET OIL 3-PHASE

ASID00522

Code		PLANET OIL 3-PHASE
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		3-phase
Voltage	V	400
Frequency	Hz	50
N. and type of turbine		1x single stage
Power	W	3000
Water lift	mmH <sub>2</sub> O	2500
Airflow	m <sup>3</sup> /h	330
Tank Capacity	l	100
Bucket sieve capacity	l	40
Diameter of inlet	mm	60
Sound Pressure Level	dB(A)	77
Dimensions (LxWxH)	mm	920x670x2000
Weight	Kg	107

### STANDARD EQUIPMENT

CODE: KTRI02521  
FILTERING KIT  
(3100 + 1500 cm<sup>2</sup>)



CODE: FTC000011  
NYLON FILTER (PA 200 μ)



CODE: SECC00113  
BUCKET SIEVE



### OPTIONAL ACCESSORIES

Anti-oil tool kit Ø50-60 mm

PMDT00449